



### ATTRIBUTES:

**LINER**  
13g Blue HDPE A6  
Basetek Liner

**COATING**  
Black Polyurethane  
Palm Coating

### FEATURES:

- Positive Grip in Dry and Light Oil Environments

### APPLICATIONS:

- Automotive Manufacturing
- Metal Stamping
- Steel Handling
- Construction
- Recycling

**Armor Guys reference number :** 02-015

### CATEGORY:

Basetek

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

### TECHNOLOGIES:



**⚠** This product can expose you to N,N-Dimethylformamide- which is known to the State of California to cause cancer. For more information go to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

### SPECIFICATIONS

LINER MATERIALS	13g Blue HDPE A6 Basetek Liner
COATING MATERIALS	Black Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	XXS-XXL

PACKAGING							
CASE SIZE	XXS	XS	S	M	L	XL	XXL
PER CARTON	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ
CASE WEIGHT	23.03/lbs	24.03/lbs	24.69/lbs	26.23/lbs	27.77/lbs	30.97/lbs	33.28/lbs
CUFF COLOR	<span style="color: pink;">■</span> Pink	<span style="color: purple;">■</span> Purple	<span style="color: red;">■</span> Red	<span style="color: yellow;">■</span> Yellow	<span style="color: brown;">■</span> Brown	<span style="color: black;">■</span> Black	<span style="color: blue;">■</span> Blue
ORIGIN	PRC						

### PERFORMANCE LEVEL

EN388: 4X44E							
ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	