

KHA 18 LTX BL 24 Quick Set ISA (600211900) Cordless Hammer
18V; Plastic Carry Case; with integrated dust extraction and Metabo Quick chuck

Order no. 600211900
EAN 4007430320681



Representative picture



- Extremely lightweight and easy to handle cordless hammer with integrated suction interface
- Maximum drilling power, efficiency, and service life with brushless technology and high-performance hammer action
- Dust-free drilling with compact dust extraction ISA 18 LTX 24
- Combination hammer with 3 functions: hammer drilling, drilling, and chiseling
- Metabo VibraTech (MVT): healthy, low-fatigue work, even in continuous use
- Metabo Quick: fast drill chuck exchange without tools for working with SDS-plus and straight shank drills
- Vario Tacho Constamatic (VTC) Electronics-Full wave electronics for drilling at customized speeds to suit the application materials, and speeds that remain almost constant even under load
- Doubly secure with electronic and mechanical safety switch-off if drill is blocked
- LED work light for optimal view of the drilling site
- Can be combined with all CAS brand 18V battery packs and chargers: www.cordless-alliance-system.com

Technical values

Parameters

| | |
|--|--------------|
| Type of battery pack | LiHD |
| Battery voltage | 18 V |
| Max. single blow energy (EPTA) | 2.2 J |
| Maximum impact rate | 4500 BPM |
| Max. capacity in concrete with hammer drills | 1 " |
| Max. capacity in masonry with core bits | 2 5/8 " |
| Max. capacity in steel | 1/2 " |
| Max. capacity in soft wood | 1 " |
| No-load speed | 0 - 1200 RPM |
| Bit retainer | SDS-plus |
| Weight without battery pack | 8.4 kg |
| Weight including battery pack | 9.7 kg |

Vibration

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 10.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 8.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 91 dB(A) |
| Sound power level (LwA) | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Integrated dust extraction ISA 18 LTX 24
 Exchangeable suction head
 Hammer chuck for tools with SDS-plus shank end
 Keyless chuck for tools with cylindrical shank end
 rubber-coated handle
 Drilling depth guide
 Plastic carrying case
 without battery pack, without charger